Title Page
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE

CHAMPION HOME BUILDERS, INC 299 N SMITH AVE CORONA, CA 92880

NOTICE

IN ACCORDANCE WITH RULE 206, THIS PERMIT TO OPERATE OR A COPY THEREOF MUST BE KEPT AT THE LOCATION FOR WHICH IT IS ISSUED.

THIS PERMIT DOES NOT AUTHORIZE THE EMISSION OF AIR CONTAMINANTS IN EXCESS OF THOSE ALLOWED BY DIVISION 26 OF THE HEALTH AND SAFETY CODE OF THE STATE OF CALIFORNIA OR THE RULES OF THE SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT. THIS PERMIT SHALL NOT BE CONSTRUED AS PERMISSION TO VIOLATE EXISTING LAWS, ORDINANCES, REGULATIONS OR STATUTES OF ANY OTHER FEDERAL, STATE OR LOCAL GOVERNMENTAL AGENCIES.

Barry R. Wallerstein, D. Env. EXECUTIVE OFFICER

By_____ Mohsen Nazemi, P.E. Deputy Executive Officer Engineering & Compliance

Table of Content

Facility ID: 163553 Revision #: 0 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

TABLE OF CONTENTS

Section	Description	Revision #	Date Issued
A	Facility Information	0	06/15/2010
В	RECLAIM Annual Emission Allocation	0	06/15/2010
C	Facility Plot Plan	TO BE DEVE	LOPED
D	Facility Description and Equipment Specific Conditions	0	06/15/2010
E	Administrative Conditions	0	06/15/2010
F	RECLAIM Monitoring and Source Testing Requirements	0	06/15/2010
G	Recordkeeping and Reporting Requirements for RECLAIM Sources	0	06/15/2010
Н	Permit To Construct and Temporary Permit to Operate	0	06/15/2010
I	Compliance Plans & Schedules	0	06/15/2010
J	Air Toxics	0	06/15/2010
K	Title V Administration	0	06/15/2010
Appendix			
A	NOx and SOx Emitting Equipment Exempt From Written Permit Pursuant to Rule 219	0	06/15/2010
В	Rule Emission Limits	0	06/15/2010

 Section A
 Page: 1

 Facility ID: 163553
 163553

 Revision #: 0
 0

 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION A: FACILITY INFORMATION

LEGAL OWNER &/OR OPERATOR:	CHAMPION HOME BUILDERS, INC

LEGAL OPERATOR (if different than owner):

EQUIPMENT LOCATION: 299 N SMITH AVE

CORONA, CA 92880-1741

MAILING ADDRESS: 299 N SMITH AVE

CORONA, CA 92880

RESPONSIBLE OFFICIAL: ROGER SCHOLTEN

TITLE: SR. VICE PRESIDENT, GENERAL COUNSEL

TELEPHONE NUMBER: (248) 614-8200

CONTACT PERSON: BENJAMIN LUCIO

TITLE: DIRECTOR OF HUMAN RESOURCES

TELEPHONE NUMBER: (951) 734-6610

TITLE V PERMIT ISSUED: June 18, 2006

TITLE V PERMIT EXPIRATION DATE: June 17, 2011

TITLE V	RECLAIM	RECLAIM	
YES	NOx:	NO	
	SOx:	NO	
	CYCLE: ZONE:	0 COASTAL	

 Section B
 Page: 1

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION B: RECLAIM ANNUAL EMISSION ALLOCATION

NOT APPLICABLE

 Section C
 Page: 1

 Facility ID:
 163553

 Revision #:
 0

 Date:
 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION C: FACILITY PLOT PLAN

(TO BE DEVELOPED)

 Section E
 Page: 1

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

The operating conditions in this section shall apply to all permitted equipment at this facility unless superseded by condition(s) listed elsewhere in this permit.

- 1. The permit shall remain effective unless this permit is suspended, revoked, modified, reissued, denied, or it is expired for nonpayment of permit processing or annual operating fees. [201, 203, 209, 301]
 - a. The permit must be renewed annually by paying annual operating fees, and the permit shall expire if annual operating fees are not paid pursuant to requirements of Rule 301(d). [301(d)]
 - b. The Permit to Construct listed in Section H shall expire one year from the Permit to Construct issuance date, unless a Permit to Construct extension has been granted by the Executive Officer or unless the equipment has been constructed and the operator has notified the Executive Officer prior to the operation of the equipment, in which case the Permit to Construct serves as a temporary Permit to Operate. [202, 205]
 - c. The Title V permit shall expire as specified under Section K of the Title V permit. The permit expiration date of the Title V facility permit does not supercede the requirements of Rule 205. [205, 3004]
- 2. The operator shall maintain all equipment in such a manner that ensures proper operation of the equipment. [204]
- 3. This permit does not authorize the emissions of air contaminants in excess of those allowed by Division 26 of the Health and Safety Code of the State of California or the Rules and Regulations of the AQMD. This permit cannot be considered as permission to violate existing laws, ordinances, regulations, or statues of other governmental agencies. [204]
- 4. The operator shall not use equipment identified in this facility permit as being connected to air pollution control equipment unless they are so vented to the identified air pollution control equipment which is in full use and which has been included in this permit. [204]

 Section E
 Page: 2

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

- 5. The operator shall not use any equipment having air pollution control device(s) incorporated within the equipment unless the air pollution control device is in full operation. [204]
- 6. The operator shall maintain records to demonstrate compliance with rules or permit conditions that limit equipment operating parameters, or the type or quantity of material processed. These records shall be made available to AQMD personnel upon request and be maintained for at least five years. [204]
- 7. The operator shall maintain and operate all equipment to ensure compliance with all emission limits as specified in this facility permit. Compliance with emission limits shall be determined according to the following specifications, unless otherwise specified by AQMD rules or permit conditions: [204]
 - a. For internal combustion engines and gas turbines, measured concentrations shall be corrected to 15 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1110.2, 1134]
 - b. For other combustion devices, measured concentrations shall be corrected to 3 percent stack-gas oxygen content on a dry basis and be averaged over a period of 15 consecutive minutes; [1146, 1146.1, 204]
 - c. For non-combustion sources, compliance with emission limits shall be determined and averaged over a period of 60 minutes; [204]
 - d. For the purpose of determining compliance with Rule 407, carbon monoxide (CO) shall be measured on a dry basis and be averaged over 15 consecutive minutes, and sulfur compounds which would exist as liquid or gas at standard conditions shall be calculated as sulfur dioxide (SO2) and be averaged over 15 consecutive minutes; [407]
 - e. For the purpose of determining compliance with Rule 409, combustion contaminant emission measurements shall be corrected to 12 percent of carbon dioxide (CO2) at standard conditions and averaged over a minimum of 15 consecutive minutes. [409]

 Section E
 Page: 3

 Facility ID: Revision #: 0
 163553

 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

- f. For the purpose of determining compliance with Rule 475, combustion contaminant emission measurements shall be corrected to 3 percent of oxygen (O2) at standard conditions and averaged over 15 consecutive minutes or any other averaging time specified by the Executive Officer. [475]
- 8. The operator shall, when a source test is required by AQMD, provide a source test protocol to AQMD no later than 60 days before the proposed test date. The test shall not commence until the protocol is approved by AQMD. The test protocol shall contain the following information: [204, 304]
 - a. Brief description of the equipment tested.
 - b. Brief process description, including maximum and normal operating temperatures, pressures, throughput, etc.
 - c. Operating conditions under which the test will be performed.
 - d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
 - e. Brief description of sampling and analytical methods used to measure each pollutant, temperature, flow rates, and moisture.
 - f. Description of calibration and quality assurance procedures.
 - g. Determination that the testing laboratory qualifies as an "independent testing laboratory" under Rule 304 (conflict of interest).
- 9. The operator shall submit a report no later than 60 days after conducting a source test, unless otherwise required by AQMD rules or equipment-specific conditions. The report shall contain the following information: [204]
 - a. The results of the source test.

 Section E
 Page: 4

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION E: ADMINISTRATIVE CONDITIONS

- b. Brief description of the equipment tested.
- c. Operating conditions under which the test was performed.
- d. Method of measuring operating parameters, such as fuel rate and process weight. Process schematic diagram showing the ports and sampling locations, including the dimensions of the ducts and stacks at the sampling locations, and distances of flow disturbances, (e.g. elbows, tees, fans, dampers) from the sampling locations (upstream and downstream).
- e. Field and laboratory data forms, strip charts and analyses.
- f. Calculations for volumetric flow rates, emission rates, control efficiency, and overall control efficiency.
- 10. The operator shall, when a source test is required, provide and maintain facilities for sampling and testing. These facilities shall comply with the requirements of AQMD Source Test Method 1.1 and 1.2. [217]
- 11. Whenever required to submit a written report, notification or other submittal to the Executive Officer, AQMD, or the District, the operator shall mail or deliver the material to: Deputy Executive Officer, Engineering and Compliance, AQMD, 21865 E. Copley Drive, Diamond Bar, CA 91765-4182. [204]

 Section F
 Page: 1

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION F: RECLAIM MONITORING AND SOURCE TESTING REQUIREMENTS

NOT APPLICABLE

Section G Page: 1 Facility ID: 163553 Revision #: 0 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION G: RECORDKEEPING AND REPORTING REQUIREMENTS FOR RECLAIM SOURCES

NOT APPLICABLE

Section H
Facility ID:
Revision #:
Date:
Page: 1
163553
0
163553
Une 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION H: PERMIT TO CONSTRUCT AND TEMPORARY PERMIT TO OPERATE

NONE

 Section I
 Page: 1

 Facility ID:
 163553

 Revision #:
 0

 Date:
 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION I: PLANS AND SCHEDULES

This section lists all plans approved by AQMD for the purposes of meeting the requirements of applicable AQMD rules.

NONE

NOTE: This section does not list compliance schedules pursuant to the requirements of Regulation XXX - Title V Permits; Rule 3004(a)(10)(C). For equipment subject to a variance, order for abatement, or alternative operating condition granted pursuant to Rule 518.2, equipment specific conditions are added to the equipment in Section D or H of the permit.

 Section J
 Page: 1

 Facility ID: 163553
 163553

 Revision #: 0
 0

 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION J: AIR TOXICS

NOT APPLICABLE

 Section K
 Page: 1

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 3

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

GENERAL PROVISIONS

- 1. This permit may be revised, revoked, reopened and reissued, or terminated for cause, or for failure to comply with regulatory requirements, permit terms, or conditions. [3004(a)(7)(C)]
- 2. This permit does not convey any property rights of any sort or any exclusive privilege. [3004(a)(7)(E)]

Permit Renewal and Expiration

- 3. (A) Except for solid waste incineration facilities subject to standards under section 129(e) of the Clean Air Act, this permit shall expire five years from the date that this Title V permit is issued. The operator's right to operate under this permit terminates at midnight on this date, unless the facility is protected by an application shield in accordance with Rule 3002(b), due to the filing of a timely and complete application for a Title V permit renewal, consistent with Rule 3003. [3004(a)(2), 3004(f)]
 - (B) A Title V permit for a solid waste incineration facility combusting municipal waste subject to standards under Section 129(e) of the Clean Air Act shall expire 12 years from the date of issuance unless such permit has been renewed pursuant to this regulation. These permits shall be reviewed by the Executive Officer at least every five years from the date of issuance. [3004(f)(2)]
- 4. To renew this permit, the operator shall submit to the Executive Officer an application for renewal at least 180 days, but not more than 545 days, prior to the expiration date of this permit. [3003(a)(6)]

Duty to Provide Information

5. The applicant for, or holder of, a Title V permit shall furnish, pursuant to Rule 3002(d) and (e), timely information and records to the Executive Officer or designee within a reasonable time as specified in writing by the Executive Officer or designee. [3004(a)(7)(F)]

Payment of Fees

6. The operator shall pay all required fees specified in Regulation III - Fees. [3004(a)(7)(G)]

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

Reopening for Cause

- 7. The Executive Officer will reopen and revise this permit if any of the following circumstances occur:
 - (A) Additional regulatory requirements become applicable with a remaining permit term of three or more years. Reopening is not required if the effective date of the requirement is later than the expiration date of this permit, unless the permit or any of its terms and conditions has been extended pursuant to paragraph (f)(4) of Rule 3004.
 - (B) The Executive Officer or EPA Administrator determines that this permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
 - (C) The Executive Officer or EPA Administrator determines that the permit must be revised or revoked to assure compliance with the applicable requirements. [3005(g)(1)]

COMPLIANCE PROVISIONS

- 8. The operator shall comply with all regulatory requirements, and all permit terms and conditions, except:
 - (A) As provided for by the emergency provisions of condition no. 17 or condition no. 18, or
 - (B) As provided by an alternative operating condition granted pursuant to a federally approved (SIP-approved) Rule 518.2.

Any non-compliance with any federally enforceable permit condition constitutes a violation of the Federal Clean Air Act and is grounds for enforcement action; for permit termination, revocation and reissuance, or revision; or denial of a permit renewal application. Non-compliance may also be grounds for civil or criminal penalties under the California State Health and Safety Code. [3004(a)(7)(A)]

 Section K
 Page: 3

 Facility ID: Revision #: Date:
 163553

 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

- 9. The operator shall allow the Executive Officer or authorized representative, upon presentation of appropriate credentials to:
 - (A) Enter the operator's premises where emission-related activities are conducted, or records are kept under the conditions of this permit;
 - (B) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
 - (C) Inspect at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
 - (D) Sample or monitor at reasonable times, substances or parameters for the purpose of assuring compliance with the facility permit or regulatory requirements. [3004(a)(10)(B)]
- 10. All terms and conditions in this permit, including any provisions designed to limit a facility's potential to emit, are enforceable by the EPA Administrator and citizens under the federal Clean Air Act, unless the term or condition is designated as not federally enforceable. Each day during any portion of which a violation occurs is a separate offense. [3004(g)]
- 11. A challenge to any permit condition or requirement raised by EPA, the operator, or any other person, shall not invalidate or otherwise affect the remaining portions of this permit. [3007(b)]
- 12. The filing of any application for a permit revision, revocation, or termination, or a notification of planned changes or anticipated non-compliance does not stay any permit condition. [3004(a)(7)(D)]
- 13. It shall not be a defense for a person in an enforcement action, including those listed in Rule 3002(c)(2), that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit, except as provided for in "Emergency Provisions" of this section. [3004(a)(7)(H)]

 Section K
 Page: 4

 Facility ID: 163553
 163553

 Revision #: 0
 0

 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

- 14. The operator shall not build, erect, install, or use any equipment, the use of which, without resulting in a reduction in the total release of air contaminants to atmosphere, reduces or conceals an emission which would otherwise constitute a violation of Chapter 3 (commencing with Section 41700) of Part 4, of Division 26 of the California Health and Safety Code or of AQMD rules. This rule shall not apply to cases in which the only violation involved is of Section 41700 of the California Health and Safety Code, or Rule 402 of AQMD Rules. [408]
- 15. Nothing in this permit or in any permit shield can alter or affect:
 - (A) Under Section 303 of the federal Clean Air Act, the provisions for emergency orders;
 - (B) The liability of the operator for any violation of applicable requirements prior to or at the time of permit issuance;
 - (C) The applicable requirements of the Acid Rain Program, Regulation XXXI;
 - (D) The ability of EPA to obtain information from the operator pursuant to Section 114 of the federal Clean Air Act;
 - (E) The applicability of state or local requirements that are not "applicable requirements", as defined in Rule 3000, at the time of permit issuance but which do apply to the facility, such as toxics requirements unique to the State; and
 - (F) The applicability of regulatory requirements with compliance dates after the permit issuance date. [3004(c)(3)]
- 16. For any portable equipment that requires an AQMD or state permit or registration, excluding a) portable engines, b) military tactical support equipment and c) AQMD-permitted portable equipment that are not a major source, are not located at the facility for more than 12 consecutive months after commencing operation, and whose operation does not conflict with the terms or conditions of this Title V permit: 1) the facility operator shall keep a copy of the AQMD or state permit or registration; 2) the equipment operator shall comply with the conditions on the permit or registration and all other regulatory requirements; and 3) the facility operator shall treat the permit or registration as a part of its Title V permit, subject to recordkeeping, reporting and certification requirements. [3004(a)(1)]

 Section K
 Page: 5

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration **EMERGENCY PROVISIONS**

- 17. An emergency¹ constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limit only if:
 - (A) Properly signed, contemporaneous operating records or other credible evidence demonstrate that:
 - (1) An emergency occurred and the operator can identify the cause(s) of the emergency;
 - (2) The facility was operated properly (i.e. operated and maintained in accordance with the manufacturer's specifications, and in compliance with all regulatory requirements or a compliance plan), before the emergency occurred;
 - (3) The operator took all reasonable steps to minimize levels of emissions that exceeded emissions standard, or other requirements in the permit; and,
 - (4) The operator submitted a written notice of the emergency to the AQMD within two working days of the time when the emissions limitations were exceeded due to the emergency. The notice shall contain a description of the emergency, any steps taken to mitigate emissions, and corrective actions taken; and
 - (B) The operator complies with the breakdown provisions of Rule 430 Breakdown Provisions, or subdivision (i) of Rule 2004 Requirements, whichever is applicable. [3002(g), 430, 2004(i)]
- 18. The operator is excused from complying with any regulatory requirement that is suspended by the Executive Officer during a state of emergency or state of war emergency, in accordance with Rule 118 Emergencies. [118]

^{1 &}quot;Emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the operator, including acts of God, which: (A) requires immediate corrective action to restore normal operation; and (B) causes the facility to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency; and (C) is not caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

 Section K
 Page: 6

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 3

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration **RECORDKEEPING PROVISIONS**

- 19. In addition to any other recordkeeping requirements specified elsewhere in this permit, the operator shall keep records of required monitoring information, where applicable, that include:
 - (A) The date, place as defined in the Title V permit, and time of sampling or measurements;
 - (B) The date(s) analyses were performed;
 - (C) The company or entity that performed the analyses;
 - (D) The analytical techniques or methods used;
 - (E) The results of such analyses; and
 - (F) The operating conditions as existing at the time of sampling or measurement. [3004(a)(4)(B)]
- 20. The operator shall maintain records pursuant to Rule 109 and any applicable material safety data sheet (MSDS) for any equipment claimed to be exempt from a written permit by Rule 219 based on the information in those records. [219(t)]
- 21. The operator shall keep all records of monitoring data required by this permit or by regulatory requirements for a period of at least five years from the date of the monitoring sample, measurement, report, or application. [3004(a)(4)(E)]

REPORTING PROVISIONS

- 22. The operator shall comply with the following requirements for prompt reporting of deviations:
 - (A) Breakdowns shall be reported as required by Rule 430 Breakdown Provisions or subdivision (i) of Rule 2004 Requirements, whichever is applicable.

 Section K
 Page: 7

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 3

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

- (B) Other deviations from permit or applicable rule emission limitations, equipment operating conditions, or work practice standards, determined by observation or by any monitoring or testing required by the permit or applicable rules that result in emissions greater than those allowed by the permit or applicable rules shall be reported within 72 hours (unless a shorter reporting period is specified in an applicable State or Federal Regulation) of discovery of the deviation by contacting AQMD enforcement personnel assigned to this facility or otherwise calling (800) CUT-SMOG.
- (C) A written report of such deviations reported pursuant to (B), and any corrective actions or preventative measures taken, shall be submitted to AQMD, in an AQMD approved format, within 14 days of discovery of the deviation.
- (D) All other deviations shall be reported with the monitoring report required by condition no. 23. [3004(a)(5)]
- 23. Unless more frequent reporting of monitoring results are specified in other permit conditions or in regulatory requirements, the operator shall submit reports of any required monitoring to the AQMD at least twice per year. The report shall include a) a statement whether all monitoring required by the permit was conducted; and b) identification of all instances of deviations from permit or regulatory requirements. A report for the first six calendar months of the year is due by August 31 and a report for the last six calendar months of the year is due by February 28. [3004(a)(4)(F)]
- 24. The operator shall submit to the Executive Officer and to the Environmental Protection Agency (EPA), an annual compliance certification. For RECLAIM facilities, the certification is due when the Annual Permit Emissions Program (APEP) report is due and shall cover the same reporting period. For other facilities, the certification is due on March 1 for the previous calendar year. The certification need not include the period preceding the date the initial Title V permit was issued. Each compliance certification shall include:
 - (A) Identification of each permit term or condition that is the basis of the certification;

Section K Page: 8
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

- (B) The compliance status during the reporting period;
- (C) Whether compliance was continuous or intermittent;
- (D) The method(s) used to determine compliance over the reporting period and currently, and
- (E) Any other facts specifically required by the Executive Officer to determine compliance.

The EPA copy of the certification shall be sent to: Director of the Air Division Attn: Air-3 USEPA, Region IX 75 Hawthorne St. San Francisco, CA 94105 [3004(a)(10)(E)]

25. All records, reports, and documents required to be submitted by a Title V operator to AQMD or EPA shall contain a certification of accuracy consistent with Rule 3003(c)(7) by a responsible official (as defined in Rule 3000). [3004(a)(12)]

PERIODIC MONITORING

26. All periodic monitoring required by this permit pursuant to Rule 3004(a)(4)(c) is based on the requirements and justifications in the AQMD document "Periodic Monitoring Guidelines for Title V Facilities" or in case-by-case determinations documented in the TitleV application file. [3004(a)(4)]

 Section K
 Page: 9

 Facility ID: Revision #: 0
 163553

 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

FACILITY RULES

This facility is subject to the following rules and regulations

With the exception of Rule 402, 473, 477, 1118 and Rules 1401 through 1420, the following rules that are designated as non-federally enforceable are pending EPA approval as part of the state implementation plan. Upon the effective date of that approval, the approved rule(s) will become federally enforceable, and any earlier versions of those rules will no longer be federally enforceable.

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 109	5-2-2003	Federally enforceable
RULE 1107	1-6-2006	Non federally enforceable
RULE 1107	11-9-2001	Federally enforceable
RULE 1113	11-8-1996	Federally enforceable
RULE 1113	7-9-2004	Non federally enforceable
RULE 1122	10-1-2004	Federally enforceable
RULE 1132	3-5-2004	Federally enforceable
RULE 1132	5-7-2004	Non federally enforceable
RULE 1136	6-14-1996	Federally enforceable
RULE 1168	1-7-2005	Federally enforceable
RULE 1168	10-3-2003	Federally enforceable
RULE 1171	11-7-2003	Federally enforceable
RULE 118	12-7-1995	Non federally enforceable
RULE 1303(a)(1)-BACT	12-6-2002	Non federally enforceable
RULE 1303(a)(1)-BACT	5-10-1996	Federally enforceable
RULE 1303(b)(2)-Offset	12-6-2002	Non federally enforceable
RULE 1303(b)(2)-Offset	5-10-1996	Federally enforceable
RULE 1401	12-7-1990	Non federally enforceable
RULE 1401	7-10-1998	Non federally enforceable
RULE 204	10-8-1993	Federally enforceable
RULE 217	1-5-1990	Federally enforceable
RULE 219	7-11-2003	Non federally enforceable

 Section K
 Page: 10

 Facility ID: Revision #: Date:
 163553

 June 15, 2010
 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

SECTION K: TITLE V Administration

RULE SOURCE	Adopted/Amended Date	FEDERAL Enforceability
RULE 219	9-4-1981	Federally enforceable
RULE 3002	11-14-1997	Federally enforceable
RULE 3003	11-14-1997	Federally enforceable
RULE 3003	3-16-2001	Non federally enforceable
RULE 3004	12-12-1997	Federally enforceable
RULE 3004(a)(4)-Periodic	12-12-1997	Federally enforceable
Monitoring		
RULE 3005	11-14-1997	Federally enforceable
RULE 3005	3-16-2001	Non federally enforceable
RULE 3007	10-8-1993	Federally enforceable
RULE 304	6-3-2005	Non federally enforceable
RULE 401	11-9-2001	Non federally enforceable
RULE 401	3-2-1984	Federally enforceable
RULE 402	5-7-1976	Non federally enforceable
RULE 404	2-7-1986	Federally enforceable
RULE 408	5-7-1976	Federally enforceable
RULE 430	7-12-1996	Non federally enforceable
RULE 442	12-15-2000	Federally enforceable
RULE 443	5-7-1976	Federally enforceable
RULE 481	1-11-2002	Federally enforceable
RULE 701	6-13-1997	Federally enforceable
40CFR 63 Subpart MMMM	1-2-2004	Federally enforceable

Appendix A Page: 1 Facility ID: 163553 Revision #: 0 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX A: NOX AND SOX EMITTING EQUIPMENT EXEMPT FROM WRITTEN PERMIT PURSUANT TO RULE 219

NONE

Appendix B Page: 1 Facility ID: 163553 Revision #: 0 Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates									
Coating		Air-	Dried			Ba	ıked		
	gr	n/l	lb/	'gal	gr	n/l	lb/	/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07	
General One-	275	275	2.3	2.3	275	275	2.3	2.3	
Component									
General Multi-	340	340	2.8	2.8	275	275	2.3	2.3	
Component									
Military	340	340	2.8	2.8	275	275	2.3	2.3	
Specification									
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5	
Solar-	420	420	3.5	3.5	360	360	3.0	3.0	
Absorbent									
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0	
Extreme High-	420	340	3.5	2.8	360	360	3.0	3.0	
Gloss									
Metallic	420	420	3.5	3.5	420	420	3.5	3.5	

Appendix B Page: 2 Facility ID: 163553 Revision #: 0 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont.

Effective Dates, cont.											
Coating	oating Air-Dried						Baked				
	gm	ı/l	lb/gal gm/l		gm/l		lb	/gal			
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07			
Extreme	420	420	3.5	3.5	360	360	3.0	3.0			
Performance											
Prefabricated	420	275	3.5	2.3	275	275	2.3	2.3			
Architectural											
One-Component											
Prefabricated	420	340	3.5	2.8	275	275	2.3	2.3			
Architectural											
Multi-											
Component											
Touch Up	420	420	3.5	3.5	360	360	3.0	3.0			
Repair	420	420	3.5	3.5	360	360	3.0	3.0			
Silicone Release	420	420	3.5	3.5	420	420	3.5	3.5			
High-	420	420	3.5	3.5	420	420	3.5	3.5			
Performance											
Architectural											
Camouflage	420	420	3.5	3.5	420	420	3.5	3.5			
Vacuum-	420	420	3.5	3.5	420	420	3.5	3.5			
Metalizing											
Mold-Seal	420	420	3.5	3.5	420	420	3.5	3.5			
High-	420	420	3.5	3.5	420	420	3.5	3.5			
Temperature											
Electric-	420	420	3.5	3.5	420	420	3.5	3.5			
Insulating											
Varnish											
Pan Backing	420	420	3.5	3.5	420	420	3.5	3.5			
Pretreatment	420	420	3.5	3.5	420	420	3.5	3.5			
Coatings											

Appendix B Page: 3
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 01-06-2006]

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates									
Coating		Air-	Dried			В	aked		
	gı	n/l	lb/	'gal	gı	n/l	lb/	/gal	
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07	
General One- Component	275	275	2.3	2.3	275	275	2.3	2.3	
General Multi- Component	340	340	2.8	2.8	275	275	2.3	2.3	
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3	
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5	
Solar- Absorbent	420	420	3.5	3.5	360	360	3.0	3.0	
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0	
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0	
Metallic	420	420	3.5	3.5	420	420	3.5	3.5	

Appendix B Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

Except as otherwise provided in Rule 1107

(1) VOC Content of Coatings

A person shall not apply to metal parts and products subject to the provisions of this rule any coatings, including any VOC-containing materials added to the original coating supplied by the manufacturer, which contain VOC in excess of the limits specified below:

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates									
Coating		Air-]	Dried			Ba	ıked		
	gr	n/l	lb/	'gal	gr	n/l	lb/gal		
	Current	7/1/07	Current	7/1/07	Current	7/1/07	Current	7/1/07	
General One- Component	275	275	2.3	2.3	275	275	2.3	2.3	
General Multi- Component	340	340	2.8	2.8	275	275	2.3	2.3	
Military Specification	340	340	2.8	2.8	275	275	2.3	2.3	
Etching Filler	420	420	3.5	3.5	420	420	3.5	3.5	
Solar- Absorbent	420	420	3.5	3.5	360	360	3.0	3.0	
Heat-Resistant	420	420	3.5	3.5	360	360	3.0	3.0	
Extreme High-Gloss	420	340	3.5	2.8	360	360	3.0	3.0	
Metallic	420	420	3.5	3.5	420	420	3.5	3.5	

Appendix B Page: 6
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1107 11-09-2001]

VOC LIMITS Less Water and Less Exempt Compounds Effective Dates, cont. Baked Coating Air-Dried gm/l gm/l lb/gal lb/gal Cur 7/1/07 Current 7/1/07 Current 7/1/07 Current 7/1/07 rent 3.5 3.5 Extreme 420 420 360 360 3.0 3.0 Performance 275 3.5 275 Prefabricated 420 2.3 275 23 23 Architectural One-Component 420 340 275 275 Prefabricated 3.5 2.8 2.3 2.3 Architectural Multi-Component 420 420 3.5 3.5 360 360 3.0 3.0 Touch Up Repair 420 420 3.5 3.5 360 360 3.0 3.0 Silicone Release 420 420 3.5 3.5 420 3.5 3.5 420 High-Performance 3.5 3.5 3.5 3.5 420 420 420 420 Architectural Camouflage 420 420 3.5 3.5 420 3.5 3.5 420 420 420 3.5 3.5 3.5 3.5 Vacuum-420 420 Metalizing Mold-Seal 420 420 3.5 3.5 420 420 3.5 3.5 3.5 3.5 420 420 3.5 420 420 3.5 High-Temperature Electric-Insulating 420 420 3.5 3.5 420 420 3.5 3.5 Varnish Pan Backing 420 420 3.5 3.5 420 420 3.5 3.5 420 3.5 3.5 3.5 Pretreatment 420 3.5 420 420

(2) A person shall not use VOC-containing materials which have a VOC content of more than 200 grams per liter of material for stripping any coating governed by this rule.

Coatings

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

- (1) Except as provided in paragraphs (c)(2), (c)(3), and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, or solicit the application of, any architectural coating which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, or manufacture, blend, or repackage such a coating for use within the District.
- (2) Except as provided in paragraphs (c)(3) and (c)(4) of Rule 1113, the operator shall not supply, sell, offer for sale, apply, solicit the application of, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified.

TABLE OF STANDARDS

VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water And Less Exempt Compounds

COATING	Limit*	Effective Date of Adoption	Effective 1/1/1998	Effective 1/1/1999	Effective 7/1/2001	Effective 1/1/2005	Effective 7/1/2008
Bond Breakers Clear Wood Finishes Varnish Sanding Sealers Lacquer Concrete-Curing Compounds Dry-Fog Coatings Fire-proofing Exterior Coatings Fire-Retardant Coatings Clear Pigmented Flats Graphic Arts (Sign) Coatings	350 350 350 680 350 400 350 650 350 250 500	450	550	350	100	275	50

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 11-08-1996]

	L		11 00 1//	~ 1		
Industrial Maintenance Primers and Topcoats						
Alkyds	420					
Catalyzed Epoxy	420					
Bituminous Coatings	420					
Materials	720					
Inorganic Polymers	420					
Vinyl Chloride Polymers	420					
Chlorinated Rubber	420					
Acrylic Polymers	420					
Urethane Polymers	420					
Silicones	420					
Unique Vehicles	420					
Japans/Faux Finishing	350	700		350		
Coatings	550	, 55		000		
Magnesite Cement Coatings	600			450		
Mastic Coatings	300					
Metallic Pigmented Coatings	500					
Multi-Color Coatings	420		250			
Pigmented Lacquer	680		550		275	
Pre-Treatment Wash Primers	780					
Primers, Sealers, and	350					
Undercoaters						
Quick-Dry Enamels	400					
Roof Coatings	300					
Shellac						
Clear	730					
Pigmented	550					
Stains	350					
Swimming Pool Coatings						
Repair	650					
Other	340					
Traffic Coatings	250		150			
Waterproofing Sealers	400					
Wood Preservatives	250					
Below-Ground	350					
Other	350					

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards

TABLE OF STANDARDS (cont.)

VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

Appendix B Page: 9
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-09-2004]

- (1) Except as provided in paragraphs (c)(2), (c)(3), (c)(4), and specified coatings averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage any architectural coating for use in the District which, at the time of sale or manufacture, contains more than 250 grams of VOC per liter of coating (2.08 pounds per gallon), less water, less exempt compounds, and less any colorant added to tint bases, and no person shall apply or solicit the application of any architectural coating within the District that exceeds 250 grams of VOC per liter of coating as calculated in this paragraph.
- Except as provided in paragraphs (c)(3), (c)(4), and designated coatings (2) averaged under (c)(6), no person shall supply, sell, offer for sale, manufacture, blend, or repackage, for use within the District, any architectural coating listed in the Table of Standards which contains VOC (excluding any colorant added to tint bases) in excess of the corresponding VOC limit specified in the table, after the effective date specified, and no person shall apply or solicit the application of any architectural coating within the District that exceeds the VOC limit as specified in this paragraph. No person shall apply or solicit the application within the District of any industrial maintenance coatings for residential use or for use in areas such as office space and meeting rooms of industrial, commercial or institutional facilities not exposed to such extreme environmental conditions described in the definition of industrial maintenance coatings; or of any rust-preventative coating for industrial use, unless such a rust preventative coating complies with the Industrial Maintenance Coating VOC limit specified in the Table of Standards.

Appendix B Page: 10 Facility ID: 163553 Revision #: 0 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-09-2004] TABLE OF STANDARDS VOC LIMITS

Grams of VOC Per Liter of Coating, Less Water and Less Exempt Compounds

COATING	Limit Effective Date									
	*	1/1/98	1/1/99	7/1/01	1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Bond Breakers	350									
Clear Wood Finishes										
Varnish	350							275		
Sanding Sealers	350							275		
Lacquer	680	550					275			
Clear Brushing Lacquer	680						275			
Concrete-Curing Compounds	350									
Dry-Fog Coatings	400									
Fire-Proofing Exterior Coatings	450		350							
Fire-Retardant Coatings										
Clear	650									
Pigmented	350									
Flats	250			100						50
Floor Coatings	420				100			50		
Graphic Arts (Sign) Coatings	500									
Industrial Maintenance (IM) Coatings	420					250		100		
High Temperature IM Coatings**					420					
Zinc-Rich IM Primers	420				340			100		
Japans/Faux Finishing Coatings	700		350							
Magnesite Cement Coatings	600		450							
Mastic Coatings	300									
Metallic Pigmented Coatings	500									
Multi-Color Coatings	420	250								
Non-Flat Coatings	250				150			50		
Pigmented Lacquer	680	550					275			
Pre-Treatment Wash Primers	780				420					
Primers, Sealers, and Undercoaters	350				200			100		
Quick-Dry Enamels	400				250			50		

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1113 07-09-2004]

COATING	Limit Effective Date									
	*	1/1/98	1/1/99	7/1/01	1/1/03	1/1/04	1/1/05	7/1/06	7/1/07	7/1/08
Quick-Dry Primers, Sealers, and Undercoaters	350				200			100		
Recycled Coatings					250					
Roof Coatings	300				250		50			
Roof Coatings, Aluminum	500						100			
Roof Primers, Bituminous	350				350					
Rust Preventative Coatings	420				400			100		
Shellac										
Clear	730									
Pigmented	550									
Specialty Primers	350							100		
Stains	350				250				100	
Stains, Interior	250									
Swimming Pool Coatings										
Repair	650				340					
Other	340									
Traffic Coatings	250	150								
Waterproofing Sealers	400				250			100		
Waterproofing Concrete/Masonry Sealers	400							100		
Wood Preservatives										
Below-Ground	350									
Other	350									

The specified limits remain in effect unless revised limits are listed in subsequent columns in the Table of Standards The National VOC Standard at 650~g/l is applicable until 1/1/2003*

**

TABLE OF STANDARDS (cont.) VOC LIMITS

Grams of VOC Per Liter of Material

COATING	Limit
Low-Solids Coating	120

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Except as otherwise provided in Rule 1136

(a) The operator shall not apply any coating to a wood product which has a VOC content, including any VOC-containing material added to the original coating supplied by the manufacturer, which exceeds the applicable limit specified below:

(1) **VOC LIMITS**Grams Per Liter (lb/gal) of Coating, [lbs VOC/lb of solids],
Less Water and Less Exempt Compounds

COATING	Com	uaut I iusit	On and After 7/1/2005
<u>COATING</u>	<u>Cur</u> I	<u>rent Limit</u> or II	<u>//1/2005</u>
Clear Sealers	550 (4.6) [1.39]	680 (5.7) [3.36]	275 (2.3) [0.36]
Clear Topcoat	550 (4.6) [1.37]	275 (2.3) [0.35]	275 (2.3) [0.35]
Pigmented Primers, Sealers & Undercoats	550 (4.6) [1.06]	600 (5.0) [1.08]	275 (2.3) [0.21]
Pigmented Topcoats	550 (4.6) [1.10]	275 (2.3) [0.25]	275 (2.3) [0.25]

The operator shall use coatings on a wood product that comply with either all VOC limits in column I or all VOC limits in column II. The operator that applies a primer, sealer or undercoat, but not a topcoat, to a wood product, shall be subject to column I for that wood product.

(2) Notwithstanding the requirements of clause (a)(1), an operator that applies a topcoat and a primer, sealer or undercoat to a shutter may, until July 1, 2005, choose to comply with the VOC limits specified below for that shutter:

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

VOC LIMITS

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids], <u>Less Water and Less Exempt Compounds</u>

COATING

Clear Sealers	275 (2.3) [0.36]
Clear Topcoat	680 (5.7) [2.99]
Pigmented Primers, Sealers & Undercoats	275 (2.3) [0.33]
Pigmented Topcoats	600 (5.0) [1.38]

(3) **VOC LIMITS**

Grams Per Liter, (lb/gal) of Coating, [lbs VOC/lb of solids], Less Water and Less Exempt Compounds

		On and After
COATING	Current Limit	<u>7/1/2005</u>
Barrier Coat - Plastic Components	760 (6.3) [3.9]	275 (2.3) [0.28]
Composite Wood Edge Filler	550 (4.6) [1.15]	275 (2.3) [0.31]
Extreme Performance Coatings	420 (3.5) [0.51]	275 (2.3) [0.33]
Fillers	500 (4.2) [0.66]	275 (2.3) [0.18]
High-Solid Stains	550 (4.6) [1.23]	350 (2.9) [0.42]
Inks	500 (4.2) [0.96]	500 (4.2) [0.96]
Mold-Seal Coatings	750 (6.3) [4.2]	750 (6.3) [4.2]
Multi-Colored Coatings	685 (5.7) [2.6]	275 (2.3) [0.33]

VOC LIMITS

Grams Per Liter (lb/gal) of Material

		On and After
<u>COATING</u>	Current Limit	<u>7/1/2005</u>
Low-Solids Barrier Coat - Plastic Components	760 (6.3)	120 (1.0)
Low-Solid Stains, Toners, and Washcoats	480 (4.0)	120 (1.0)

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1136 06-14-1996]

Any coating subject to this rule that meets any of the three VOC limit formats (grams per liter, lb/gal, or lbs VOC/lb of solids) is in compliance with this subparagraph.

- (4) The VOC limit for japan coatings is 700 grams per liter of coatings, less water and exempt compounds, as applied.
- (b) A person shall not use a stripper on wood products unless:
 - (1) it contains less than 350 grams of VOC per liter of material; or
 - (2) the VOC composite vapor pressure is 2 mm Hg (0.04 psia) or less at 20°C (68°F).

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit*
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

Specialty Applications	VOC Limits and Effective Dates**			
	Current VOC Limit*	1-1-05	7-1-05	1-1-07
PVC Welding	510			
CPVC Welding	490			
ABS Welding	400		325	
Plastic Cement Welding	350	250		
Adhesive Primer for Plastic	650		550	
Computer Diskette Manufacturing	350			
Contact Adhesive	80			
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	540			250

^{**} The specified limits remain in effect unless revised limits are listed in subsequent columns.

Appendix B Page: 17
Facility ID: 163553
Revision #: 0
Date: June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

For adhesives, adhesive bonding primers, or any other primer not regulated by the above two tables and applied to the following substrates, the following limits shall apply:

Substrate Specific Applications	Current VOC Limit*
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit*
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 01-07-2005]

Sealant Primers	Current VOC Limit*
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

^{*} For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

- (1) Unless otherwise specified in paragraph (c)(2), a person shall not apply any adhesives, adhesive bonding primers, adhesive primers, or any other primer which have a VOC content in excess of 250 g/L less water and less exempt compounds.
- (2) A person shall not apply adhesives, adhesive bonding primers, adhesive primers, sealants, sealant primers, or any other primer which have a VOC content in excess of the limits specified below:

VOC Limit*, Less Water and Less Exempt Compounds in Grams per Liter

Architectural Applications	Current VOC Limit
Indoor Carpet Adhesives	50
Carpet Pad Adhesives	50
Outdoor Carpet Adhesives	150
Wood Flooring Adhesive	100
Rubber Floor Adhesives	60
Subfloor Adhesives	50
Ceramic Tile Adhesives	65
VCT and Asphalt Tile Adhesives	50
Dry Wall and Panel Adhesives	50
Cove Base Adhesives	50
Multipurpose Construction Adhesives	70
Structural Glazing Adhesives	100
Single Ply Roof Membrane Adhesives	250

^{*} For low-solid adhesives or sealants the VOC limit is expressed in grams per liter of material as determined in paragraph (b)(32); for all other adhesives and sealants, VOC limits are expressed as grams of VOC per liter of adhesive or sealant less water and less exempt compounds as determined in paragraph (b)(31).

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

.Specialty Applications	VOC Limits and Effective Dates**			es**
	Current VOC Limit	6-7-02	1-1-03	1-1-05
PVC Welding	510			285
CPVC Welding	490			270
ABS Welding	400			
Plastic Cement Welding	350			250
Adhesive Primer for Plastic	650			250
Computer Diskette Manufacturing	350			
Contact Adhesive	250		80	
Special Purpose Contact Adhesive	250			
Tire Retread	100			
Adhesive Primer for Traffic Marking Tape	150			
Structural Wood Member Adhesive	140			
Sheet Applied Rubber Lining Operations	850			
Top and Trim Adhesive	250	540		250

^{**} The specified limits remain in effect unless revised limits are listed in subsequent columns.

APPENDIX B: RULE EMISSION LIMITS [RULE 1168 10-03-2003]

Substrate Specific Applications	Current VOC Limit
Metal to Metal	30
Plastic Foams	50
Porous Material (except wood)	50
Wood	30
Fiberglass	80

If an adhesive is used to bond dissimilar substrates together the adhesive with the highest VOC content shall be allowed.

Sealants	Current VOC Limit
Architectural	250
Marine Deck	760
Nonmembrane Roof	300
Roadway	250
Single-Ply Roof Membrane	450
Other	420

Sealant Primers	Current VOC Limit
Architectural	
Non Porous	250
Porous	775
Modified Bituminous	500
Marine Deck	760
Other	750

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)
(iii) Medical Devices & Pharmaceuticals	800 (6.7)
(B) Repair and Maintenance Cleaning	
(i) General	25 (0.21)
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

[ROLL 11/111 0/ 2000]	
SOLVENT CLEANING ACTIVITY	CURRENT LIMITS VOC g/l (lb/gal)
(iii) Medical Devices & Pharmaceuticals	
(A) Tools, Equipment, & Machinery	800 (6.7)
(B) General Work Surfaces	600 (5.0)
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)
(D) Cleaning of Ink Application Equipment	
(i) General	25 (0.21)
(ii) Flexographic Printing	25 (0.21)
(iii) Gravure Printing	
(A) Publication	750 (6.3)
(B) Packaging	25 (0.21)
(iv) Lithographic or Letter Press Printing	

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 11-07-2003]

	CURRENT LIMITS
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)
(A) Roller Wash – Step 1	600 (5.0)
(B) Roller Wash-Step 2, Blanket Wash, & On-Press Components	800 (6.7)
(C) Removable Press Components	25 (0.21)
(v) Screen Printing	750 (6.3)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)
(vii) Specialty Flexographic Printing	600 (5.0)
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-06-2005]

(1) Solvent Requirements

A person shall not use a solvent to perform solvent cleaning operations unless the solvent complies with the applicable requirements set forth below:

	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Product Cleaning During Manufacturing Process Or Surface Preparation For Coating, Adhesive, Or Ink Application			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	500 (4.2)	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals	800 (6.7)		
(B) Repair and Maintenance Cleaning			
(i) General	25 (0.21)		
(ii) Electrical Apparatus Components & Electronic Components	900 (7.5)	100 (0.83)	
(iii) Medical Devices & Pharmaceuticals			

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-06-2005]

	DE 11/1 05-00-2		
	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(A) Tools, Equipment, & Machinery	800 (6.7)		
(B) General Work Surfaces	600 (5.0)		
(C) Cleaning of Coatings or Adhesives Application Equipment	550 (4.6)	25 (0.21)	
(D) Cleaning of Ink Application Equipment			
(i) General	25 (0.21)		
(ii) Flexographic Printing	25 (0.21)		
(iii) Gravure Printing			
(A) Publication	750 (6.3)	100 (0.83)	
(B) Packaging	25 (0.21)		
(iv) Lithographic or Letter Press Printing			
(A) Roller Wash – Step 1	600 (5.0)	500 (4.2)	100 (0.83)
(B) Roller Wash-Step 2, Blanket Wash, & On- Press Components	800 (6.7)	500 (4.2)	100 (0.83)

APPENDIX B: RULE EMISSION LIMITS [RULE 1171 05-06-2005]

		•	
	CURRENT LIMITS*	Effective 7/1/2005*	Effective 7/1/2006
SOLVENT CLEANING ACTIVITY	VOC g/l (lb/gal)	VOC g/l (lb/gal)	VOC g/l (lb/gal)
(C) Removable Press Components	25 (0.21)		
(v) Screen Printing	750 (6.3)	500 (4.2)	100 (0.83)
(vi) Ultraviolet Ink/ Electron Beam Ink Application Equipment (except screen printing)	800 (6.7)	500 (4.2)	100 (0.83)
(vii) Specialty Flexographic Printing	600 (5.0)	100 (0.83)	
(E) Cleaning of Polyester Resin Application Equipment	25 (0.21)		

^{*} The specified limits remain in effect unless revised limits are listed in subsequent columns.

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

The operator shall not discharge into the atmosphere from this equipment, particulate matter in excess of the concentration at standard conditions, shown in Table 404(a). Where the volume discharged is between figures listed in the Table, the exact concentration permitted to be discharged shall be determined by linear interpolation.

For the purposes of this rule, emissions shall be averaged over one complete cycle of operation or one hour, whichever is the lesser time period.

TABLE 404(a)

Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Concentration of Particulate Matter"Allowed in Discharged Gas Calculated as Dry Gas at Standard Conditions		Volume Discharged Calculated as Dry Gas At Standard Conditions		Maximum Co of Particula Allowed in E Gas Calculated at Standard Co	te Matter Discharged I as Dry Gas
Cubic	Cubic	Milligrams	Grains per	Cubic	Cubic	Milligrams	Grains per
meters	feet	per	Cubic Foot	meters	feet	per	Cubic
Per	Per	Cubic		Per Minute	Per	Cubic Meter	Foot
Minute	Minute	Meter			Minute		
25 or	883	450	0.196	900	31780	118	0.0515
	or						
less	less						
30	1059	420	.183	1000	35310	113	.0493
35	1236	397	.173	1100	38850	109	.0476
40	1413	377	.165	1200	42380	106	.0463
45	1589	361	.158	1300	45910	102	.0445

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

Volume Di Calculated Ga At Star Condit	d as Dry Discharged Gas Calculated as Dry Gas At Standard Conditions Gas at Standard		Maximum Concentration of Particulate Matter Allowed in Discharged Gas Calculated as Dry Ga at Standard Conditions				
Cubic	Cubic	Milligrams	Grains per	Cubic	Cubic	Milligrams	Grains per
meters	feet	per	Cubic Foot	meters	feet	per	Cubic
Per	Per	Cubic		Per Minute	Per	Cubic Meter	Foot
Minute	Minute	Meter			Minute		
50	1766	347	.152	1400	49440	100	.0437
60	2119	324	.141	1500	52970	97	.0424
70	2472	306	.134	1750	61800	92	.0402
80	2825	291	.127	2000	70630	87	.0380
90	3178	279	.122	2250	79460	83	.0362
100	3531	267	.117	2500	88290	80	.0349
125	4414	246	.107	3000	105900	75	.0327
150	5297	230	.100	4000	141300	67	.0293
175	6180	217	.0947	5000	176600	62	.0271
200	7063	206	.0900	6000	211900	58	.0253
250	8829	190	.0830	8000	282500	52	.0227
300	10590	177	.0773	10000	353100	48	.0210
350	12360	167	.0730	15000	529700	41	.0179
400	14130	159	.0694	20000	706300	37	.0162
450	15890	152	.0664	25000	882900	34	.0148

Appendix B Page: 30 Facility ID: 163553 Revision #: 0 June 15, 2010

FACILITY PERMIT TO OPERATE CHAMPION HOME BUILDERS, INC

APPENDIX B: RULE EMISSION LIMITS [RULE 404 02-07-1986]

			oncentration iculate			Maximum Co of Particula		
Volume Discharged		Matter"Allowed in		Volume D	Volume Discharged		Allowed in Discharged	
Calculated	9		ged Gas	Calculated a	as Dry Gas	Gas Calculated	l as Dry Gas	
Ga	S	Calculate	ed as Dry	At Standard	Conditions	at		
At Star	ıdard	Gas at S	Standard			Standard Co	onditions	
Condit	ions	Cond	itions					
Cubic	Cubic	Milligrams	Grains per	Cubic	Cubic	Milligrams	Grains per	
meters	feet	per	Cubic Foot	meters	feet	per	Cubic	
Per	Per	Cubic		Per Minute	Per	Cubic Meter	Foot	
Minute	Minute	Meter			Minute			
500	17660	146	.0637	30000	1059000	32	.0140	
600	21190	137	.0598	40000	1413000	28	.0122	
700	24720	129	.0563	50000	1766000	26	.0114	
800	28250	123	.0537	70000 or more	2472000 or more	23	.0100	